

## Label, highly flexible - MM-EMLF (EX10)R C1 WH/BK - 0803937

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Label, highly flexible, Roll, white, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: adhesive, lettering field size: continuous x 10 mm

### Your advantages

- ✔ Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- ✔ The self-adhesive material in continuous format is particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing
- ✔ Thanks to the continuous format, a label of the appropriate length can be created flexibly for the relevant application
- ✔ The material is cUL certified
- ✔ High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 212166
GTIN	4055626212166
Weight per Piece (excluding packing)	58.400 g
Weight per piece (including packing)	59.200 g
Custom tariff number	96121010
Country of origin	China

### Technical data

#### Dimensions

Length (b)	8000 mm
Width (a)	10 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 75 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

# Label, highly flexible - MM-EMLF (EX10)R C1 WH/BK - 0803937

## Technical data

### General

Color	white
Components	Free from silicone and cadmium
Material	Vinyl polymer
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Marking mounting type	adhesive

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27400629
eCl@ss 11.0	27281103
eCl@ss 4.0	24190200
eCl@ss 4.1	24190200
eCl@ss 5.0	27149100
eCl@ss 5.1	27141100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149129
eCl@ss 9.0	27400629

### ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761
ETIM 6.0	EC001288
ETIM 7.0	EC001288

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504

## Label, highly flexible - MM-EMLF (EX10)R C1 WH/BK - 0803937

### Approvals

Approvals

---

Approvals

cULus Recognized

---

Ex Approvals

---

### Approval details

cULus Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

MH48542