

Label, highly flexible - MM-EMLF (EX12)R C1 GN/WH - 0803952

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Label, highly flexible, Roll, green, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: adhesive, lettering field size: continuous x 12 mm

Your advantages

- Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- The self-adhesive material in continuous format is particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing
- Thanks to the continuous format, a label of the appropriate length can be created flexibly for the relevant application
- High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing



Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|--------------------------------|
| GTIN | 4 055626 212296 |
| GTIN | 4055626212296 |
| Weight per Piece (excluding packing) | 59.500 g |
| Weight per piece (including packing) | 61.220 g |
| Custom tariff number | 96121010 |
| Country of origin | China |
| Note | Made to Order (non-returnable) |

Technical data

Dimensions

| Length (b) | 8000 mm |
|------------|---------|
| Width (a) | 12 mm |

Ambient conditions

| Ambient temperature (operation) | -20 °C 75 °C |
|---------------------------------|---|
| Recommended storage conditions | 20°C/50% relative humidity. Storage in the original packaging is recommended. |



Label, highly flexible - MM-EMLF (EX12)R C1 GN/WH - 0803952

Technical data

General

| Color | green |
|-----------------------|--------------------------------|
| Components | Free from silicone and cadmium |
| Material | Vinyl polymer |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Marking mounting type | adhesive |

Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| eCl@ss 10.0.1 | 27400629 |
|---------------|----------|
| eCl@ss 11.0 | 27281103 |
| eCl@ss 4.0 | 24190200 |
| eCl@ss 4.1 | 24190200 |
| eCl@ss 5.0 | 27149100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27149100 |
| eCl@ss 7.0 | 27149129 |
| eCl@ss 9.0 | 27400629 |

ETIM

| ETIM 2.0 | EC000761 |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

UNSPSC

| UNSPSC 6.01 | 30211811 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39131504 |
| UNSPSC 18.0 | 39131504 |
| UNSPSC 19.0 | 39131504 |
| UNSPSC 20.0 | 39131504 |
| UNSPSC 21.0 | 39131504 |



Phoenix Contact 2021 © - all rights reserved http://www.phoenixcontact.com