

# Replacement die - CRIMPFOX-M RCI 2,5/DIE - 1212074

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Die, for Crimpfox-M, for insulated cable lugs 0.5 - 1.5 mm<sup>2</sup> and 1.5 - 2.5 mm<sup>2</sup> (red, blue), packed in a serial storage box

## Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4046356452533
Weight per Piece (excluding packing)	74.200 g
Weight per piece (including packing)	74.200 g
Custom tariff number	82032000
Country of origin	Germany

## Technical data

### Dimensions

Length (b)	114 mm
Width (a)	75 mm
Height (c)	25.5 mm

### General

Color	black
Compression	Oval crimp
Type of contact	Insulated cable lugs
Designation	Crimping position 1
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	1.5 mm <sup>2</sup>
AWG min	22
AWG max	16
Designation	Crimping position 2
Min. cross section	1.5 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>
AWG min	16
AWG max	14

# Replacement die - CRIMPFOX-M RCI 2,5/DIE - 1212074

## Technical data

### General

Weight	75 g
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	2.5 mm <sup>2</sup>

## Classifications

### eCl@ss

eCl@ss 10.0.1	21019290
eCl@ss 4.0	21040300
eCl@ss 4.1	21040300
eCl@ss 5.0	21040300
eCl@ss 5.1	21040300
eCl@ss 6.0	21043800
eCl@ss 7.0	21043811
eCl@ss 8.0	21043811
eCl@ss 9.0	21019290

### ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001282
ETIM 5.0	EC001282
ETIM 6.0	EC001282
ETIM 7.0	EC001282

### UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518
UNSPSC 19.0	27111518

## Approvals

### Approvals

---

Approvals

EAC

---

## Replacement die - CRIMPFOX-M RCI 2,5/DIE - 1212074

### Approvals

Ex Approvals

---

#### Approval details

EAC



RU x-  
DE.xx08.B.02974