

## Plug-in bridge - FBS 2-10 - 3005947

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in bridge, pitch: 10.2 mm, number of positions: 2, color: red

### Why buy this product

- ✔ The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

### Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	
GTIN	4017918168759
Weight per Piece (excluding packing)	7.040 g
Weight per piece (including packing)	7.050 g
Custom tariff number	85389099
Country of origin	Poland

### Technical data

#### Technical data

Color	red
Material	Copper
Number of positions	2
Pitch	10.2 mm
Flammability rating according to UL 94	V0
Maximum load current	50 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

# Plug-in bridge - FBS 2-10 - 3005947

## Technical data

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

### ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489
ETIM 6.0	EC000489

### UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

### Approval details

## Plug-in bridge - FBS 2-10 - 3005947

### Approvals

EAC



EAC-Zulassung