

SIPLUS CMS-Hardware MCN11 "Media converter node;" 1 opt. and 1 electr. "interfaces;" "UW=24 V DC; IP67"



General information

| | |
|--------------------------|--|
| Product type designation | MCN11 |
| Product description | MCN11 physically converts data to be transferred from one medium (electric) to another (optic) and vice versa. MCN11 can span distances from 4.5 meters to 500 meters. |

Installation type/mounting

| | |
|--|--|
| Mounting type | standard rail |
| Mounting accessories | Mounting bracket, can be ordered as option |
| Required clearance | |
| • for side-by-side mounting at the front | 80 mm |
| • for side-by-side mounting at the top | 25 mm |
| • for side-by-side mounting at the back | 25 mm |

Power

| | |
|--------------------------|-------|
| Active power input, max. | 0.6 W |
|--------------------------|-------|

Interfaces

| | |
|---------------------------------|-----------------------------|
| Number of IEEE 1394a interfaces | 1 |
| • Transmission rate | 400 Mbit/s |
| • Design of plug-in connection | Male connector 8-pole (M12) |

| | |
|--|--|
| Number of IEEE 1394b interface, optical | 1 |
| • Transmission rate | 400 Mbit/s |
| • Design of plug-in connection | Duplex SC 62.5 / 125 µm multimode fiber (MMF) |
| • Wavelength | 850 nm |
| Protocols | |
| IEEE 1394a | Yes |
| IEEE 1394b optical | Yes |
| Degree and class of protection | |
| IP degree of protection | IP67 |
| Standards, approvals, certificates | |
| Certificate of suitability | CE |
| CE mark | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| China RoHS compliance | Yes |
| Use in hazardous areas | |
| • ATEX | Yes |
| • IECEx | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | 0 °C |
| • max. | 65 °C |
| Ambient temperature during storage/transportation | |
| • Storage, min. | -40 °C |
| • Storage, max. | 85 °C |
| • Transportation, min. | -40 °C |
| • Transportation, max. | 85 °C |
| Cables | |
| Design of the data cable | Pre-assembled 8-pole cable with shield |
| Design of FOC fiber | 50 / 125 µm MMF up to 500 m length, 62.5 / 125 µm MMF up to 220 m length |
| Connection method | |
| Design of electrical connection for the PE conductor | M4 screw on the front panel: SHIELD |
| Mechanics/material | |
| Material of housing | aluminum |
| Dimensions | |
| Width | 46 mm |
| Height | 160 mm |

| | |
|--------------------------------|------------|
| Depth | 56 mm |
| Depth when mounted on DIN rail | 65 mm |
| Weights | |
| Weight (without packaging) | 0.46 kg |
| last modified: | 05/28/2020 |