

SIDOOR ATE531S Control device for Platform doors, with protective coating, with fan, up to 280 kg door weight, 1*RS485, 5*DI, 2*DO, -25 - +70 °C PROFINET IO Conformance Class C via 2x RJ45 sockets



Figure similar

General information	
Product type designation	ATE531S
Optional product expansion	Standard mounting rail holder 6FB1144-0AT00-3AS0
Manufacturer's article no. of the usable motor	6FB1203-0AT12-7DA0
Manufacturer's article no. of the usable power supply unit	6FB1112-0AT20-2TR0
Mean time between failures (MTBF)	13 y
Installation type/mounting	
Installation and mounting instructions	No direct exposure to the sun
Supply voltage	
Design of the power supply	Via SIDOOR TRANSFORMER or via DC
Rated value (DC)	36 V; with MED280: at 24 V DC max. door speed of 500 mm/s, at 28.8 V DC max. door speed of 800 mm/s. With MEG251: at 24 V DC max. door speed of 500 mm/s, at 28.8 V DC max. door speed of 750 mm/s
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	37.1 V

Protection in case of DC supply	Use of a circuit breaker in the supply path according to 60898-1, 8A, C-characteristic type SIEMENS: 5SY4108-7 or 5SY4108-7KK11
---------------------------------	---

Encoder supply

Output voltage (DC)	24 V; Ensure correct polarity! CAUTION: Do not supply with external voltage!
short-circuit proof	Yes
Overload-proof	Yes
24 V encoder supply	
• Output current, max.	400 mA

Power

Active power input	80 W
Active power input, max.	540 W
Active power input (standby mode)	7 W

Digital inputs

Control inputs isolated	Yes
Control inputs p-switching	Yes
Input voltage	
• permissible voltage at input, min.	10 V; Observe polarity !
• permissible voltage at input, max.	28 V; Observe polarity !
Input current	
• for signal "1", min.	3 mA
• for signal "1", max.	15 mA

Digital outputs

Relay outputs	
Switching capacity of contacts	
— at 30 V DC, min.	0.01 A
— at 30 V DC, max.	0.5 A

Mechanical data

Opening width of door, min.	0.35 m
Opening width of door, max.	5 m
Weight of door, max.	280 kg
Operating cycle frequency of door, max.	180 1/h
Kinetic energy, max.	75 J

Interfaces

Interfaces/bus type	PROFINET according to Conformance Class A, B, C; integrated switch for linear and ring structure
---------------------	--

Isolation

Overvoltage category	2
----------------------	---

Degree and class of protection

IP degree of protection	IP20
-------------------------	------

Standards, approvals, certificates

CE mark	No
UL approval	No
China RoHS compliance	Yes
Standard for EMC	EN 61000-6-2 / EN 61000-6-4 / EN 61326-3-1 / EN 50121-3-2 / EN50121-4 / EN50121-5
Standard for safety	EN 60950-1 / EN 60335-1 / EN 14752 / EN ISO 13849-1 Cat. 2 PL d / IEC 62061: SIL 2

Ambient conditions

Ambient temperature during operation

• min.	-25 °C
• max.	70 °C
• Remark	to ensure compliance with MTBF value, ensure that the ambient temperature is less than 50 °C for 90 % of operating time and screw the control unit onto a metallic mounting surface in a manner that ensures thermal conductivity or use standard rail mounting. At operating temperatures above 50 °C, the maximum output current of the 24 V DC output is a maximum of 0.1 A and the maximum number of cycles is 60/h

Ambient temperature during storage/transportation

• Storage, min.	-40 °C
• Storage, max.	85 °C

Altitude during operation relating to sea level

• Installation altitude above sea level, max.	2 000 m
---	---------

Relative humidity

• No condensation, min.	10 %
• No condensation, max.	93 %

Dimensions

Width	320 mm
Height	60 mm
Depth	80 mm

last modified: 06/22/2020