

MV500 built-in ring I. red basic For MV500 devices (MLFB: 6GF3540-0CD10, -0GE10, 6GF3550-0CD10, -0GE10, 6GF3560-0HE10, -0LE10) Lighting: LED 618 Nm, Lighting distance up to 0.8 m; Assembly material enclosed; Use with protective lens barrel (MLFB: 6GF3540-8AC11)



Figure similar

Mechanical data	
Material	Aluminum/glass
Color	black
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	0 ... 50 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-30 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-30 ... +70 °C
Further information / Internet-Links	
Internet-Link	
<ul style="list-style-type: none"> <li>to website: TIA Selection Tool</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
<ul style="list-style-type: none"> <li>to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="https://support.industry.siemens.com/WW/view/en/67384964">https://support.industry.siemens.com/WW/view/en/67384964</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/codereader">http://www.siemens.com/codereader</a>
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>

- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

05/08/2020