

### Product type designation

Product description

### IE FC M12 Cable Connector PRO (PROFINET)

M12 connector with socket insert with high protection class, 8-pole, X-coded

IE FC M12 Cable Connector PRO 4x 2 M12 plug-in connectors that can be assembled in the field (X-coded); 8-pole; metal enclosure; FC quick-connect technology; Female contact insert; 1 pack=8 units



### Suitability for use

For connecting electrical cables to SCALANCE W (M12 gigabit interface) for fast assembly with the FastConnect system

### Transfer rate

Transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10000 Mbit/s

### Interfaces

Number of electrical connections

- for Industrial Ethernet FC TP cables 8
- for network components or terminal equipment 1

Type of electrical connection

- for Industrial Ethernet FC TP cables integrated cut-and-clamp contacts for 8-wire TP FC installation cable AWG24
- for network components or terminal equipment M12 connector (X-coded)

Type of electrical connection / FastConnect

Yes

### Mechanical data

Material / of the enclosure

metal

Locking mechanism design

Screw

Design, dimensions and weights	
Type of cable outlet	180° cable outlet
Width	16.8 mm
Height	16.8 mm
Depth	49 mm
Net weight	40 g
Connectable cable cross-section	6.5 ... 8 mm

Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +85 °C
Chemical resistance	
<ul style="list-style-type: none"> <li>to water</li> </ul>	resistant
Protection class IP	IP65/67

Product features, product functions, product components / general	
Product feature	
<ul style="list-style-type: none"> <li>PoE capability</li> </ul>	Yes
<ul style="list-style-type: none"> <li>PoE+capability</li> </ul>	Yes
<ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes
Product component	
<ul style="list-style-type: none"> <li>strain relief</li> </ul>	Yes

Standards, specifications, approvals	
Certificate of suitability	
<ul style="list-style-type: none"> <li>RoHS conformity</li> </ul>	Yes
<ul style="list-style-type: none"> <li>UL approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>cULus approval</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Railway application in accordance with EN 50155</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Fire protection in accordance with EN 45545-2</li> </ul>	Yes
Standard for structured cabling	Cat6A

Further information / Internet-Links	
Internet-Link	
<ul style="list-style-type: none"> <li>to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>to website: CAx Download Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

last modified:

06/24/2020