

### Product type designation

### Antenna ANT 3S

RF300/RF200 antenna ANT 3 NO for connection to RF250R, RF350R and RF350M (GEN1) IP67, -25 to +70 °C, dimensions 50x28x 10 mm for the transponders MDS D117, MDS D127, MDS D421, MDS D521



Suitability for operation	RF250R / RF300 with small transponders
<b>Radio frequencies</b>	
Transmission frequency / Rated value	13.56 MHz
<b>Electrical data</b>	
Type of electrical connection / of the antenna	M8, 4-pin
Design of plug-in connection	female
<b>Mechanical data</b>	
Material	PA6 V0
Color	black
Tightening torque / of the screw for securing the equipment / maximum	1 N·m
Mounting distance	0 m
<ul style="list-style-type: none"> <li>relating to metal surfaces / recommended / minimum</li> </ul>	
<b>Ambient conditions</b>	
Ambient temperature	-25 ... +70 °C
<ul style="list-style-type: none"> <li>during operation</li> </ul>	

<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +85 °C
Protection class IP	IP67
Shock resistance	according to EN 60721-3-7 Class 7M2
Shock acceleration	500 m/s <sup>2</sup>
Vibrational acceleration	200 m/s <sup>2</sup>

Design, dimensions and weights	
Width	28 mm
Height	50 mm
Depth	10 mm
Net weight	35 g
Mounting type	2 x M4 screws

Standards, specifications, approvals	
Certificate of suitability	CE, FCC, IC, cULus
Certificate of suitability <ul style="list-style-type: none"> <li>• IECEx</li> </ul>	Yes

accessories	
accessories	Antenna cable

Further information / Internet-Links	
Internet-Link <ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx Download Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/67384964">https://support.industry.siemens.com/cs/ww/en/view/67384964</a> <a href="http://www.siemens.com/ident/rfid">http://www.siemens.com/ident/rfid</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	05/12/2020