

SIMATIC RF200/RF300 antenna ANT 30 stainless steel; IP67, -25 to +70 °C, thread M30x1.5, length 40 mm; with trailing antenna wire, both ends pluggable PUR, UL 758, length 3 m



Figure similar

Suitability for operation	RF250R / RF350R / RF350M
Radio frequencies	
Transmission frequency / Rated value	13.56 MHz
Electrical data	
Type of electrical connection / of the antenna	M8, 4-pole (at supplied cable)
Design of plug-in connection	male
Mechanical data	
Material	Stainless steel V2A
Color	Silver
Tightening torque / of the screw for securing the equipment / maximum	3 N·m
Mounting distance	0 m
<ul style="list-style-type: none"> relating to metal surfaces / recommended / minimum 	
Ambient conditions	
Ambient temperature	

<ul style="list-style-type: none"> • during operation 	-25 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> • during transport 	-40 ... +85 °C
Protection class IP	IP67
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weights

Depth	38 mm
Diameter	30 mm
Net weight	95 g
Mounting type	2 x stainless steel nuts M30 x 1.5
Wire length / of antenna cable	3 m

Standards, specifications, approvals

Certificate of suitability	CE, cULus
Certificate of suitability <ul style="list-style-type: none"> • IECEx 	Yes

accessories

accessories	Included: 6GT2391-0AH30 (antenna cable)
-------------	---

Further information / Internet-Links

Internet-Link <ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com
last modified:	05/12/2020